







GPI04192023

MARKSMAN [™]10

The ultimate in convenience and portability, this unit requires no power, being fully operated by the efforts of the operator pushing the pack through the unit. It can be placed on top of a desk or table for use, and can be stored under the table or standing in a corner or closet when not in use. The unit has the ability to be adjusted for different package sizes and formats.

Machine Features

Standard

• GPI standard lock

Frame

• Anodized aluminum or plastic components

Guards

• Not required as this is a manually operated machine with no inherent dangers

Optional

Mobile stand

Changeover

Simple changeover to a variety of heights and diameters of various products

Time

5-30 minutes, depending on many variables

Specifications

Standard Machine Elevation Table-top system

Machine Weight Approx. 100lbs (45 kg)


Air Requirements None Required


Electrical None Required

Ancillary Equipment

Custom infeed and discharge equipment available







Primary Container Size Ranges

Bottles, glass and plastic Cans (2 piece and 3 piece) Cups, pharmaceuticals, aerosols, etc.

Diameter: 0.79" (20mm) to 5.91" (150mm) Height: 0.79" (20mm) to 12.6" (320 mm)

Pack Formats

1x2, 1x3, 1x4, 1x5, 1x6 2x2, 2x3, 2x4, 2x5, 2x6 Multi-layered product is possible when the container is stackable

MM10



Pack Styles

Standard: Over the Crown, Neck Through, Straight Wrap Optional: Ad-panel, Handle Wrap Full Tucked AD Panel

Speed / Pitches

Ideally suited for multi-packaging operations with low volume needs such as market trials or special products and containers.

Packaging from 6 to 15 packs per minute is realistic. These speeds depend upon product type and operator dexterity.



Graphic Packaging International 1500 Riveredge Parkway NW, #100 Atlanta, GA 30328 +1 (770) 240-7200 Please visit our website at graphicpkg.com for more information. © Copyright 2021, Graphic Packaging International. All rights reserved.